

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/008444 A2

(51) International Patent Classification⁷: G11B 7/135, 7/24

(21) International Application Number:
PCT/IB2003/002726

(22) International Filing Date: 25 June 2003 (25.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02077754.6 10 July 2002 (10.07.2002) EP

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VAN DER MARK,

Martinus, B. [NL/NL]; c/o Prof. Holstlaan, NL-5656 AA Eindhoven (NL). PHILIPS, Gavin, N. [GB/NL]; c/o Prof. Holstlaan, NL-5656 AA Eindhoven (NL).


(74) Agent: DEGUELLE, Wilhelmus, H., G.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: OPTICAL RECORDING AND READING SYSTEM, OPTICAL DATA STORAGE MEDIUM AND USE OF SUCH MEDIUM



(57) Abstract: An optical recording and reading system for use with an optical data storage medium (5) is described. The system comprises the medium (5) having a recording stack (9), formed on a substrate (8). The recording stack (9) is suitable for recording by means of a focused radiation beam (1) with a wavelength λ in air. The recording stack (9) has a first optical surface (6) most remote from the substrate (8). An optical head (3), with an objective (2) having a numerical aperture $NA > 0.8$ and from which objective (2) the focused radiation beam emanates (1) during recording, is (2) arranged on the recording stack (9) side of said optical data storage medium (5). The objective has a second optical surface (7) closest to the recording stack (9), and is adapted for recording/reading at a free working distance d_F of smaller than $50 \mu m$ from the first optical surface (6). At least one of the first optical surface (6) and the second optical surface (7) is provided with a transparent hydrophobic layer (10) that has a refractive index n and has a thickness smaller than $0.5vn$. In this way reliable recording and reading is achieved, specifically contamination build-up on the second optical surface (7) is prevented or counteracted.

BEST AVAILABLE COPY